

RUSCO®

HINGE PROVISIONS
FOR TEMPLATED OR NON
TEMPLATED HINGES WITH
RADIUS OR SQUARE CORNERS

U.L. AND
WARNOCK HERSEY
APPROVED 90 MINUTE

INTEGRAL KERF
FOR WATHERSTRIP

* 3/8" X 3/4"
OBLONG SLOT
FOR MOLDING
INSTALLATION

9/64" DIA.
INSTALLATION
NAIL HOLE

JF 65
FIRE RATED
COMPRESSION
WEATHER-STRIP
OR
MAGNETIC
FIRE RATED
WEATHER-STRIP

NOTE: FRAME IS
PRE-HANGABLE
AND ADJUSTABLE
FOR WALLS FROM
4-1/16" TO 8-1/16"
THICK.

U.L. AND
WARNOCK HERSEY
APPROVED UP TO
1-1/2 HRS. UP TO
3668 SIZE.

NOTE: WEATHERSTRIP
IS PRESSURE FITTED
INTO INTEGRAL
KERF, WITHOUT
USE OF
ADHESIVES

FOR TRIMMING
OUT WITH
YOUR CHOICE
OF WOOD
MOLDING BRICK,
OR MOLDING

AVAILABLE
GAUGES:
16, 18 & 20

HINGE REINFORCEMENT
PROJECTION WELDED TO
FRAME IN (6) PLACES

2-1/8"

UNIQUE COINED INSTALLATION
HOLES FOR SHIMLESS
INSTALLATION USING #10
PANHEAD SCREWS PROVIDED

PATENT NOS. 4,912,879 & 4,912,880